

LS 4000-T 12V



Optional






GENERATORE A BENZINA - 4 TEMPI

Generatore per 2 abbacchiatori elettrici con motorino a gestione elettronica, con motore a scoppio 4 tempi a benzina, flangiato ad un alternatore a 2 poli monofase. Sistema di regolazione brushless a condensatore. Avviamento con autoavvolgente ed elettrico a batteria. Pannello alternatore con 2 prese monofase CEE 16A e 1 protettore termico. Completo di quadro con 2 uscite stabilizzate a 12 Vdc adatte per abbacchiatori a gestione elettronica.

GASOLINE ENGINE GENERATOR - 4 STROKE

Generator for 2 electric harvesters with electronically controlled motor, with petrol 4-stroke petrol engine, flanged to a single-phase 2-pole alternator. Brushless condenser regulation system. Starting with recoil and electric battery. Alternator panel with 2 single-phase CEE 16A sockets and 1 thermal protector. Complete with board with 2 stabilized 12 Vdc outputs suitable for electronically managed harvesters.

MOTORE - ENGINE								
Modello Model		Potenza motore Motor power	Cilindrata Displacement	Carburante Fuel	Capacità serbatoio Tank Capacity	Rumorosità Noise db(A)		Servizio continuo orario Continuous duty running time
type		Hp / 3600 r.p.m.	cc	type	lt	LpA a 7m	LwA	h
Monocilindrico, raffreddamento ad aria, 4 - tempi Single cylinder, forced air cooling, 4 - stroke		6,5 (G 200)	196	Benzina Gasoline	3,6	70	 97	3,5

GENERATORE - GENERATOR						
Modello Model	Frequenza Frequency	Tensione Voltage	Potenza uso continuo Continuous duty power	Potenza max. Max. power	Dimensioni Dimensions	Peso Weight
	Hz.	V	kVA	kVA	mm	Kg
	50	230	3,7	4	875 x 710 x 1070	71

CARICA BATTERIA - BATTERY CHARGE Vbc 1,0 KW 12 Volt 60A